



ROSE BRAND

21 oz. Virtue Velour, FR

FABRIC SPECIFICATIONS

Weight/Linear Yard	21 oz.	Pattern Number	412
Pile Yarn & Count	30/2 Combed Cotton	Ground Yarn & Count	30/2 Combed Cotton
Pile Weight	10.5 oz./Ln Yd.	Ground Weight	5.2 oz/Ln. Yd
Pile Weight/ % of Total	50%	Ground Weight/ % of Total	50%
Pile Ends/Inch.	58	Ground Ends/Inch.	58
Pile Tufts/Sq. Inch.	1450	Filling Yarn & Count	20/2 Cotton
Pile Height/1000"	95	Filling Weight	5.2 oz/Ln. Yd
		Filling Picks/Inch	50

PERFORMANCE

This Fabric Meets or Exceeds The Listed Standard Requirements

<u>Test</u>	<u>Standard Requirements</u>	<u>Test Method</u>
Abrasion (Heavy Duty)	30,000 double rubs ANSI/ASTM-D-3597-77	ASTM-D-1175-71-24 Wyzenbeek Test
Tensile Strength: Warp: Filling:	50 Lbs. Min. 50 Lbs. Min. ANSI/ASTM-D-3597-77	ASTM-D-1682
Tear Strength:	6 Lbs. Min. 6 Lbs. Min. ANSI/ASTM-D-3597-77	ASTM-D-2262
Crocking:	Class 4 Dry Min. Class 3 Med. Min. ANSI/ASTM-D-3597-77	AATCC-8-1974
Light Fastness:	Fading 60 Hours	AATCC-16A-1974

FLAMMABILITY

Manufactured To Meet The Following Requirements
MVS 302
BIFMA F-1-1978
SC-191-53 Class1 California
UFAC Class 1
AC 25.853 (Special Coating Must be Requested)
NFPA 701



ROSE BRAND NY (800) 223 - 1624 CA (800) 360 - 5056

www.rosebrand.com