



ROSE BRAND

FABRIC SPECIFICATIONS

Pattern Name	Apollo	Pattern Number	626
Weight/Linear Yard	12.9 Oz.	Ground Yarn & Count	150/66/1FR Poly
Pile Yarn & Count	150/66/1FR Poly	Ground Weight	0.120
Pile Weight	0.4313	Ground Weight/ % of Total	46%
Pile Weight/ % of Total	54%	Ground Ends/Inch.	51
Pile Ends/Inch.	51	Filling Yarn & Count	150/66/1FR Poly
Pile Tufts/Sq. Inch.	1785	Filling Weight	0.255
Pile Height/1000"	110	Filling Picks/Inch	105

PERFORMANCE

This Fabric Meets or Exceeds The Listed Standard Requirements

<u>Test</u>	<u>Standard Requirements</u>	<u>Test Method</u>
Abrasion (Heavy Duty)	50,000 double rubs ANSI/ASTM-D-3597-02	ASTM-D-4157-02 Wyzenbeek Test
Tensil Strength: Warp: Filling:	50 Lbs. Min. 50 Lbs. Min. ANSI/ASTM-D-3597-02	ASTM-D-1682
Tear Strength:	6 Lbs. Min. 6 Lbs. Min. ANSI/ASTM-D-3597-02	ASTM-D-2262
Crocking:	Class 4 Dry Min. Class 3 Med. Min. ANSI/ASTM-D-3597-02	AATCC-8--2001
Light Fastness:	Fading 60 Hours	AATCC-16-2003

FLAMMABILITY

Manufactured To Meet The Following Requirements

NFPA 701
MVS 302
BIFMA F-1-1978
SC-191-53 Class1 California
UFAC Class 1