

96-D Allen Boulevard Farmingdale, New York 11735-5626 USA Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956 e-mail: info@govmark.com

Page 1

Received:05/07/2007 Completed:05/11/2007 Letter: A2	rb P.O. #:	Test R	.eport #: 2-0	7624-2-
Client's Avora Lining, Black. 100% VISA Intrinsic Pole	lyester. 54" Wide	2		
Tested For: Bob Bertrand, Gen. Mgr.		Key Test: NFPA 701-89	9 Sm	95
Rose Brand 4 Emerson Lane Secaucus, NJ 07094		Tel: 1-(212)-242-7 Fax: 1-(212)-242-7		

PC: 1H

TEST PERFORMED: NFPA 701 - Standard Methods of Fire Tests for Flame Resistant Textiles and Films 1989 Edition (Small Scale Procedure for Curtains & Draperies Weighing Less than 10 oz/yd²)

Note: NFPA 701 - 1989 Edition has been superseded by NFPA 701 - 1996 Edition. However, the 1989 Edition still remains in effect in that some of the older building codes call for testing by the 1989 Edition.

RESULTS REPORTED: [x] Initially

[] After 3 dry cleanings

[] After 5 launderings @ 160°F

RESULTS:

RESOLIS:	Specimen #	Afterflame* (seconds)	Flaming Drip (seconds)	Char Length (inches)
1				
Length:	1	8.0	0.0	4.2
	2	7.0	0.0	5.6
	3	0.0	0.0	3.7
	4	1.7	2.0	4.3
	5	6.5	0.0	4.8
Width:	6	5.8	0.0	5.5
	7	5.8	0.0	6.1
	8	5.9	0.0	6.8
	9	0.0	0.0	5.4
	10	0.0	0.0	4.9
			Avg: 0.2	Avg: 5.1

APPROXIMATE WEIGHT OF MATERIAL (as measured by Govmark): 5.2 oz/yd²

REMARKS: None.

CONCLUSION: Based on the above Results and Acceptance Criteria, the item tested:

[x] Complies; [] Does not comply; [] Requires testing of 5 additional specimens

(Page 1 of 2)



96-D Allen Boulevard Farmingdale, New York 11735-5626 USA Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956 e-mail: info@govmark.com

Page 2

Received:05/07/2007 Co	mpleted:05/11/2007 Letter: A2	rb	P.O.#:	Test Report #:	2-67624-2-
Client's Avora Lir Identification	ning, Black. 100% VISA Intrinsic Pol	yester.	54" Wide		
Tested For: Bob Bertra	and, Gen. Mgr.		Key Test: NI	FPA 701-89 Sm	95
Rose Brand			m-1. 1	(010) 242 7554	Ext: 115
4 Emerson Secaucus, N				(212)-242-7554 (212)-242-7565	Ext. 115
ACCEPTANCE CRITERIA	A :		Char Length (i	nches)	
Afterflame (seconds)	Flaming Drip (seconds) Maximum Average		Max.Avg. Max	.Ind.Spec.	
*	2.0		6.5" 7.5	11	
RETEST PROVISION: Test 5 addition		.men e	exceeds 7.5" Char Le	testing specimens	in accordance dure for Curtains
III GOVILIAN SIGNAL			- # O		
	(Paç	ge 2 (or 2)		
The state of the s					