



# ROSE BRAND

## E·N·C·O·R·E·!

### FABRIC SPECIFICATIONS

QUALITY	22 OZ. VELOUR	15 OZ. VELOUR
<p><b>COMPOSITION:</b>  <b>WIDTH:</b>  <b>WEIGHT:</b>  <b>FINISH:</b>  <b>FLAME TESTING:</b></p> <p><b>TEAR STRENGTH:</b>            Trap            (ASTM D5587)            Tongue            (ASTM D2261)</p> <p><b>TENSILE STRENGTH:</b>            Grab            (ASTM D5034)            Strip            (ASTM D5055)</p> <p><b>ABRASION:</b>            Wyzenbeek            (ASTM D3597)            Martindale            (ASTM D4966)</p> <p><b>Light Fastness:</b>            (ASTM D3597, Xenon)</p> <p><b>Crocking:</b>            (AATCC 107)</p>	<p>100% polyester            64" (162cm)            22oz./yd. (625 g/m)            Permanently FR Treatment            UFAC Class 1            NFPA 701 - Small Scale            NFPA 701 - Large Scale            NFPA 701 - 1996 Version            California Administrative Code            Title 19 Paragraph 1237.1            City of NY Bulletin No. 44</p> <p>Warp- 32 lbs (142 N)            Filling- 52 lbs (231 N)            Warp- 5 lbs (23 N)            Filling- 12 lbs (53 N)</p> <p>Warp- 60 lbs (266 N)            Filling- 147 lbs (653 N)            Warp- 23 lbs (102 N)            Filling- 100 lbs (444 N)</p> <p>Exceeds 15,000            Double Rubs            Exceeds 35,000 Cycles</p> <p>40 to 80 hrs (varies by color)</p> <p>Wet - 3 to 5 (varies by color)            Dry - 3 to 5 (varies by color)</p>	<p>100% polyester            62" (142cm)            15 oz./yd (425 g/m)            Permanently FR Treatment            UFAC Class 1            NFPA 701 - Small Scale            NFPA 701 - Large Scale            NFPA 701 - 1996 Version            California Administrative Code            Title 19 Paragraph 1237.1            City of NY Bulletin No. 44</p> <p>Warp- 16 lbs (71 N)            Filling- 13 lbs (58 N)            Warp- 4 lbs (16 N)            Filling- 12 lbs (53 N)</p> <p>Warp- 64 lbs (284 N)            Filling- 66 lbs (293 N)            Warp- 36 lbs (160 N)            Filling- 40 lbs (178 N)</p> <p>Exceeds 15,000            Double Rubs            Exceeds 35,000 Cycles</p> <p>40 to 80 hrs (varies by color)</p> <p>Wet - 3 to 5 (varies by color)            Dry - 3 to 5 (varies by color)</p>

#### CARE AND CLEANING INSTRUCTIONS

1. Regular Care - Vacuum to remove ordinary lint and dust.
2. Spot Cleaning - Most spots and stains can be removed with a damp sponge, cleaning fluids, or dry cleaning powders. None of these methods should cause spotting.
3. General Cleaning - A professional dry cleaning service is recommended for on site cleaning. Supplementary flame testing is recommended after repeated dry cleaning or washings to ensure that the curtain meets local fire codes.

PATENT PENDING