

PRODUCT DATASHEET

Product	Winch 25 Med Duty DMX Winch Part No. WAHL0006	
Description	<p>A compact cable winch with a 25Kg (55lb) load limit which can be easily controlled via DMX from a lighting desk or stand-alone controller. A simple and affordable solution to automate a wide variety of scenic elements such as curtains, practicals, flats, and light rigging solutions.</p> <p>Unlike chain motors or customized scenery winches, the Wahl Winch 25 is perfect for fast fly cues and synchronized operation via DMX control. Use multiple winches for independent control of each pick line of a contour or tab curtain. Fly in flats, doorways, ceilings and mirrors without the use of battens and fly rails -- all with the ease of control from a DMX lighting desk or stand-alone DMX controller.</p> <p>Perfect for Technical Directors, Church technicians, Shop Project Managers, Exhibit builders and decorators – virtually anyone with a need for simple, affordable and safe automation.</p>	
Features	Features <ul style="list-style-type: none"> • Compact size, with medium load capacity • Fast cable retraction • 25kg (55lb) working load • Precision control of position and speed via DMX (7 channels) 	Benefits <ul style="list-style-type: none"> • Mounts in small spaces for heavy lifting • Quick scene changes • Suitable for heavier fabric rigging, and for lifting scenic elements like chandeliers, mirrors and window units • Safe, repeatable and accurate positioning and limit settings.
Specifications	<ul style="list-style-type: none"> • 25 Kg (55lb) working load limit • 2-16 inch/sec. speed • 33ft lifting height (50ft optional) • 2mm coated wire • 16-bit DMX precision • 0.04in position accuracy 	<ul style="list-style-type: none"> • 5-pin DMX input and pass through • 7 Channels of DMX control • Powercon™ Input 230VAC input, 300 watt consumption • 15.7 x 8.9 x 11.4 in; 46lbs
Notes	<p><i>Wahlberg Winches are designed and tested for use moving light-weight scenic elements such as fabrics, small decor, props and light scenic pieces. They are not intended to be used for primary stage rigging of battens or fly-lines or any other safety-critical applications.</i></p>	

