

96-D Allen Boulevard Farmingdale, New York 11735-5626 USA Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956 e-mail: info@govmark.com

Page 1

Received: 06/01/2007 | Completed: 06/05/2007 | Letter: G3 P.O.#: rb Test Report #: 2-68078-3-Client's Poly Chintz, 100% Trevira Polyester, 58" wide. End Use: Stage Draperies & Linning of Stage Draperies. Identification Tested For: Bob Bertrand, Gen. Mgr. Key Test: CA 1237 Sm 95 Rose Brand 4 Emerson Lane **Tel:** 1-(212)-242-7554 Ext: 115 Secaucus, NJ 07094 Fax: 1-(212)-242-7565 PC: AS /jd TEST PERFORMED: California Fire Marshal Title 19: Section 1237 Fire Resistance; Small Scale Test - INTERIOR MATERIALS QUALIFICATION RESULTS REPORTED: [x] Initially [] After 3 dry cleanings [] After 5 launderings @ 160°F **RESULTS:** Afterflame Char Length Specimen # (seconds) (inches) -----------Length: 1 0 4.3 2 0 6.4 3 0 4.4Width: 4 0 4.7 5 0 4.8 6 0 5.6 Avq: 0 5.0 PRECONDITIONING: [] Standard: 1 to 1.5 hours in oven at 140°-145°F. [] Alternate for materials that distort during oven conditioning: 24 hours at 60°-80°F and 25%-50% RH. REMARKS: None. ACCEPTANCE CRITERIA: Afterflame (seconds) Char Length (inches) 1.0 maximum average 6.0 maximum average CONCLUSION: [x] The above results indicate compliance. [] The above results indicate noncompliance.



96-D Allen Boulevard Farmingdale, New York 11735-5626 USA Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956 e-mail: info@govmark.com

Page 2

Received:06/01/2007	Completed: 06/05/2007	Letter: G3	rb	P.O.#:	Test Report #:	2-6	68078-3-
Client's Poly Chintz, 100% Trevira Polyester, 58" wide. End Use: Stage Draperies & Linning of Stage Draperies. Identification							
Tested For: Bob Bertrand, Gen. Mgr. Rose Brand			Key Test: CA 1237 Sm			95	
	on Lane s, NJ 07094				1-(212)-242-7554 1-(212)-242-7565	Ext: 115	

Note: In August 1993 the State Fire Marshal issued a proposed revision, which permitted a maximum average afterflame of 4.0 seconds. This proposed revision was honored by the subsequent State Fire Marshals until approximately February 2004, at which time the State Fire Marshal's office reverted to the unrevised rule of 1 second maximum average for interior fabric; and 2.0 seconds maximum average for exterior fabric.

With regard to Char Length acceptance, please refer to Govmark's document "California Title 19 Section 1237" dated August 11, 2005.

CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified by California Fire Marshal Title 19: Section 1237 Small Scale.

AUTHORIZED SIGNATURE

THE GOVMARK ORGANIZATION, INC. /jd-

MS. HEATHER ROBERTSON

Leather E. Poherto

(Page 2 of 2)