

Rose Brand East:

4 Emerson Lane Secaucus NJ 07094 800-223-1624 201-809-1730 Fax: 201-809-1850

Rose Brand West: 10616 Lanark Street Sun Valley CA 91352

800-360-5056 818-505-6290 Fax: 818-505-6293

SPECIFICATIONS FOR PRESTIGE VELOUR

FABRIC fiber content 100% Trevira CS (polyester)

width 54" (137 cm)

unit weight 26 oz. per linear yard (737 gm/linear yard)

CONSTRUCTION thread count 48 (ground ends) x 48 (ground fill) x 51 (pile ends)

pile thread 29/2 Trevira (0.825 lbs/linear yard) ground thread 29/2 Trevira (0.43125 lbs/linear yard) fill thread 29/2 Trevira (0.41325 lbs./linear yard)

pile density 1222 pile tufts/sq. inch

pile height 95/1000"
pile percentage of weight 49%
backing percentage weight 51%
surface treatment none

Performance Testing ASTM D 4157-07: Standard Test Method for Abrasion Resistance of

Texile Fabrics (oscillatory cylinder mehtod)

Passed 50,000 cycles

FLAMMABILITY Inherently Flame Retardant (IFR)

meets requirments of:

NFPA 701 (1989), small & large scale tests

NFPA 701 (1999), test #1

California Title 19, Small Scale test

of Trevira fibers. With no harmful additives, these fibers can be recycled and have been awarded the European Oeko-Tex Standard 100 Certificate for safety and

environmental friendliness.

Care Instructions Can be washed at normal temperatures or at 71 degrees C for disinfection.

Can also be disinfected with chlorine or peroxide products without adverse effect on the fibers. Water washing or dry cleaning will not incur shrinkage.

No post wash pressing should be necessary.