



ROSE BRAND

32 oz. Royale Velour, IFR

FABRIC SPECIFICATIONS

Weight/Linear Yard	32 oz./lin yard	Pattern Number	641
Pile Yarn & Count	2/150/128 IFR Poly	Ground Yarn & Count	2/150/64 IFR Poly
Pile Weight	1.263 lbs/lin yd.	Ground Weight	0.367
Pile Weight/ % of Total	63%	Ground Weight/ % of Total	37%
Pile Ends/Inch.	51	Ground Ends/Inch.	48
Pile Tufts/Sq. Inch.	1173	Filling Yarn & Count	2/150/128 IFR poly
Pile Height/1000"	120	Filling Weight	0.367
		Filling Picks/Inch	50

PERFORMANCE

This Fabric Meets or Exceeds The Listed Standard Requirements

<u>Test</u>	<u>Standard Requirements</u>	<u>Test Method</u>
Abrasion (Heavy Duty)	50,000 double rubs ANSI/ASTM-D-3597-77	ASTM-D-1175-71-24 Wyzenbeek Test
Tensil Strength: Warp: Filling:	50 Lbs. Min. 50 Lbs. Min. ANSI/ASTM-D-3597-77	ASTM-D-1682
Tear Strength:	6 Lbs. Min. 6 Lbs. Min. ANSI/ASTM-D-3597-77	ASTM-D-2262
Crocking:	Class 4 Dry Min. Class 3 Med. Min. ANSI/ASTM-D-3597-77	AATCC-8-1974
Light Fastness:	Fading 60 Hours	AATCC-16A-1974

FLAMMABILITY

Manufactured To Meet The Following Requirements

MVS 302
 BIFMA F-1-1978
 SC-191-53 Class1 California
 UFAC Class 1
 NFPA 701
 NFPA 701



ROSE BRAND NY (800) 923 - 1624 CA (800) 360 – 5056

www.rosebrand.com