

ROSE BRAND SHOW FLOOR -- GLOSSY

Chic and sophisticated, our Show Floor—Glossy offers a dramatic option that makes a bold and dramatic statement. From entertainment venues to temporary floors and stages, Show Floor—Glossy combines a great design with the ultimate fashion statement.

STANDARD SIZES (nominal)

Overall thickness:	0.080" (2.0 mm)
Wear layer thickness:	0.018" (0.45 mm)
Roll size:	6' (1.83 m) wide x 60' (18.3 m)
Weight:	0.7 lbs./sq. ft.; 245 lbs./roll
Colors:	black, white, or red

Rose Brand offers a 10 year limited warranty.

TECHNICAL DATA

Sheet Vinyl Floor Covering w/ Backing, ASTM F1303 . . . Type 1, Grade 1, Class B	
Flexibility, ASTM F137	Pass
Hardness, ASTM D224095
James Machine, SCOF, ASTM D2047	Neolite: 0.64
Abrasion Resistance, ASTM D3884	0.54%, 1,000 cycles
Static Load (max 0.005"), ASTM F970	750 psi
Short-term indentation, ASTM F1914	0.009" residual
Castor Chair Test, ISO TR4918	25,000 cycles: Wear: 5.0, Color: 5.0; Change 5.0
Dimensional Stability, ASTM F2199017%
Heat Stability, ASTM F1514	Pass
Light Stability, ASTM F1515	Pass
Critical Radiant Flux, ASTM E648	Class 1, ≥ 0.45 watts/cm ²
Chemical Resistance, ASTM F925	Moderate Surface Attack: 5% Penol; Slight Color Change: 5% Phenol

GREEN FEATURES

- GreenMedic™: Formulated for microbial resistance
- GreenAir™: Formulated for low VOC's
- 20 – 35% post-industrial recycled content; Contributes toward LEED MR 4.1 & MR 4.2
- FloorScore® Indoor Air Quality Certified: Conforms to CA Specification 01350
- LEED Low Emitting Materials:
 - Adhesives & Sealants: IEQ Credit 4.1
 - Flooring Systems: IEQ Credit 4.3